

A Novel Architecture for a Flexible, Integrated Wideband Vector Channel Sounder for MIMO-System Investigation

Ernst Zollinger

Elektrobit AG

Rosswiesstrasse 29

CH-8608 Bubikon / ZH

Switzerland

Tel.: +41 / 55 / 253 20 71

Fax.: +41 / 55 / 253 20 70

Email: ernst.zollinger@elektrobit.ch

1 INTRODUCTION

Multipath wave propagation causes radio signals to become distorted. As the design and the performance of any wireless communication system depend on the properties of the radio channel, detailed knowledge about the channel's characteristics are indispensable. This is where radio channel sounding and investigations comes into play.

Radio channels have been measured using the pulse sounding [1], frequency sweep, and correlation techniques [2]. The correlation method has been widely used because of its interference reduction and Doppler measurement capability [3]-[5]. Cross-polarization coupling investigations of radio signals ([6]), multi-location sounding for urban vehicle-monitoring systems [7], and multi-frequency sounding using multiple sounders simultaneously [8] have a long standing tradition.

The rapidly growing interest in the directional structure of the propagation channel for wideband signals originated from the discovery that wireless systems do not necessarily suffer but might significantly profit from the inherent diversity offered by the radio environment [9]. Using antenna arrays instead of single antenna elements at one or both ends of a radio link allows to establish multiple independent channels between the terminals. These so called Single-Input Multiple-Output (SIMO) or smart antenna-systems, and Multiple-Input Multiple-Output (MIMO)-systems, respectively, promise an enhanced spectral efficiency, higher channel capacity, increased reliability of the radio link, and lower interference levels [10].

For the investigation of the spatial properties of wave propagation Kalliola and Vainikainen were first to report a channel sounding technique that scanned the output signals of the array antenna elements sequentially in time [11]. The application of this technique revealed new insights into the spatial wave propagation mechanisms [12]-[15]. This is very important regarding further developments of reliable SIMO, and MIMO channel models needed for future wideband radio systems.

This paper presents a novel architecture for a flexible, integrated wideband vector channel sounder suited for very fast time-variant Single-Input Single-Output (SISO)-, SIMO-, and MIMO radio channel investigations that can be performed simultaneously at multiple-frequencies, -locations, and different polarization of the waves at the transmitter and receiver site. This multi-dimensional channel sounder is based on an exceptional fast data acquisition and storage concept, real-time assessment of virtually any channel data during the ongoing channel measurement in the field, and bus-based modularity allowing full software control of all instrument features.

1. CHANNEL SOUNDER REQUIREMENTS

The novel architecture of the channel sounder has been deduced from the requirements originating from

- the temporal and spatial characteristics of the radio environment,
- the peculiarities of wireless communication and navigation systems, and
- the instruments modularity, flexibility, versatility, and ease-of-use within real environments.

The radio channel induced requirements concern the joint estimation of the path-loss, phase, delay, Doppler shift, Angle-of-Departure (AoD), Angle-of-Arrival (AoA), and the transfer matrix \mathbf{H} for all polarization of the multipath signals within time frames which are short compared to the coherence time of the radio channel.

Requirements emerging from terrestrial and satellite radio communication systems, wireless ad-hoc networks, and geo-location systems address the frequency ranges, duplex-modes, hand-over-schemes, multi-location capability, multi-sensor technology, and the typical user mobility profiles of these systems.

3. NOVEL CHANNEL SOUNDER ARCHITECTURE: PROPSOUND

Basic System Concept

For the measurement of the complex channel impulse response (CIR), the correlation method is chosen because of its interference reduction capability and the obtainable recording rates. Apart from periodically repeated m-sequences any other binary code sequence up to a length of 4096 chips can be generated to BPSK-(Binary Phase Shift Keying)-modulate the carrier. To enhance the versatility of the sounder in view of radio test bed applications, any complex baseband signal with bandwidths up to 200 MHz (or more [16]) can be used in the transmitter.

Multi-Dimensional Channel Sounding

The novel timing concept of the sounder paves the way to multi-dimensional channel sounding as it allows time-variant channel measurements within multiple frequency bands (for FDD channels), at multiple locations (for multi-user and geolocation systems), with multiple transmitting and receiving antenna elements (for SIMO-, and MIMO-systems), both with multiple polarization. This is accomplished by a Time Division Multiplex (TDM) technique where the multi-dimensionality of the measurements can be recorded sequentially or non-sequentially within very short time leaving space for permanent storage of the data on a hard disk until the next measurement is triggered. As switching between the TDM channels is kept to the very minimum, changes of sensitive channel parameters such as the phase, the AoD and AoA are also kept small within a single multi-dimensional channel acquisition cycle. Apart from this “sustained” recording mode, a “burst” mode has been implemented to allow for very high measurement rates within a limited period of time. Each measurement is started upon an smart internal or external (e.g. odometer) trigger whose flexibility allows to capture only the minimum required amount of channel data.

The non-sequential TDM scanning technique of the multiple sounding dimensions allows to turn the small but unavoidable phase drifts of oscillators into random phase noise. This is of importance for the spatial channel parameter estimation.

The location of the transmitter and receiver are of importance if both parts of the instrument are moved. To address this problem, the transmitter and receiver either records from its internal GPS receiver location and timing data, location marker information, or odometer data which are stored together with the time-tag information on a mass storage device for later merging them with the recorded measurement data.

High Speed Channel Sounding

The high speed measurement capability in conjunction with the TDM multi-dimensional channel sounding requires a well thought-out storage concept. It is based upon the fact that the duty cycle of a multi-dimensional measurement cycle has to be low in order to measure the time-variant behavior of the radio channel. This leads to the concept of writing the acquired data at full speed into a solid-state memory which is afterwards copied at high speed into a mass storage device before the next measurement has to be triggered. Unprocessed I and Q baseband data are stored because of the efficiency and the reusability of the measured data for different purposes and with different parameter estimation algorithms.

To enhance the data throughput to the mass storage device, multiple data acquisition units can be triggered sequentially in a “round-robin” fashion. This feature works in the sustained and the burst trigger mode of the instrument.

Real-Time Data Assessment

The measured data are simultaneously transferred to a high speed mass storage device for later post-processing and the real-time display unit to allow for on-line data assessment. This real-time quality control of the recorded data is very flexible as any data evaluation features of the post-processing software can be used within real-time display; actually the real-time display uses the same MATLAB code.

The signal processing performed within the post processing software is based on matched filter and super-resolution channel parameter estimation. Any super-resolution algorithm can be used with the sounder, however, the Space Alternating Generalized Expectation maximization (SAGE) based algorithm is implemented.

SAGE jointly estimates the path loss, path phase, delay, Doppler shift, AoD, and AoA suffered by the multipath signals [17]. The performance, i.e. the super-resolution capability, accuracy, and convergence rate of the scheme has been demonstrated in synthetic and real macro- and pico-cellular environments. The results indicate that the technique outperforms the resolution limitations of classical algorithms such as the Fourier or beam-forming method [18]. Key features of the SAGE-algorithm are:

- No temporal and/or spatial smoothing of the measured data across the array elements are required. Hence, small array with small number of elements allowing fast array scans are sufficient for many applications.
- The algorithm works with nearly any type of array antenna. No restriction on the homogeneity and the arrangements of the array elements, their radiation pattern, and coupling with other array elements matter as long as the complex radiation pattern have been measured once within an anechoic chamber. Hence, cheap array antennas can be used without compromising the accuracy of the estimated channel parameters.
- The accuracy and number of the estimated path can be traded-of versus computing time. Hence, the real-time display of the strongest paths is possible while performing the channel measurements [17].
- The SAGE-algorithms can be extended to estimate other channel parameters in a straight forward way to adapt it to the task at hand.

The power of the novel channel sounder architecture and the capability of its super-resolution algorithm will be demonstrated using synthetic and measured data.

2. SUMMARY

For performance investigations of SISO-, SIMO-, and MIMO-systems, the development of reliable MIMO channel models, and the understanding of principal propagation mechanisms found in macro-, micro-, and pico-cellular environments, corresponding channel measurement are indispensable. Starting from requirements addressed to a versatile MIMO-channel sounder a novel architecture for a flexible, integrated wideband vector channel sounder including its array antennas are presented and the impact of the signal processing used to estimate the various channel parameters on the design of the array antennas and the performance of the channel sounder are outlined.

ACKNOWLEDGEMENT

The author gratefully acknowledges the support and many useful discussions with the PropSound™ development team at Elektrobot AG (Switzerland).

REFERENCES

- [1] W.R. Young, Jr. and L.Y. Lacy, "Echoes in transmission at 450 megacycles from land-to-car radio units," *Proc. IRE*, vol. 38, pp. 255-258, March 1950.
- [2] D.C. Cox, "Delay Doppler characteristics of multipath propagation at 910 MHz in a suburban mobile radio environment," *IEEE Trans. Ant. Propag.*, vol. AP-20, no. 5, pp. 625-635, Sept. 1972.
- [3] U. Martin, R. Reng, H.W. Schüssler, and K. Schwarz, "Determination of wide-band impulse responses," Proc. 1989 URSI Intern. Symp. on Signals, Systems and Electronics, pp. 393-396, 1989.
- [4] E. Zollinger, "*Eigenschaften von Funkübertragungsstrecken in Gebäuden*", Ph.D. thesis ETH no. 10064, Swiss Federal Institute of Technology, Zürich, 1993.
- [5] Eraldo Damosso and Luis Correia (Editors), "*Digital Mobile Radio Towards Future Generation Systems*", COST 231 Final Report, European Commission, Directorate General XIII, Belgium, 1999.
- [6] D.C. Cox, R.R. Murray, HW. Arnold, A.W. Norris, and MF. Wazowicz, "Cross-polarization coupling measured for 800 MHz radio transmission in and around houses and large buildings," *IEEE Trans. Ant. and Propag.*, vol. AP-34, no. 1, pp. 83-87, January 1986.
- [7] H. Staras and St. N. Honickman, "The accuracy of vehicle location by trilateration in a dense urban environment," *IEEE Trans. Veh. Techn.*, vol. VT-21, no. 1, pp. 38 ff, Feb. 1972.
- [8] G.L. Turin, F.D. Clapp, T.L. Johnston, St.B. Fine, and D. Lavry, "A statistical model of urban multipath propagation," *IEEE Trans. Veh. Techn.*, vol VT-21, no. 1, pp. 1-9, Feb. 1972.
- [9] M. Steinbauer, A.F. Molisch, A. Burr, and R. Thomä, "MIMO channel capacity based on measurement results", EWCS 2000, Oct. 2-6, Paris.
- [10] J. B. Andersen, "Antenna arrays in mobile communications: gain, diversity, and channel capacity," *IEEE Trans. Information Theory*, vol. 44, pp. 744-765, 1998.
- [11] K. Kalliola and P. Vainikainen, "Characterization system for radio channel of adaptive array antennas," Personal Indoor and Mobile Radio Conference, PIMRC'97, session C4 on smart antennas, presentation C4.5, Sept. 1-4, Helsinki, Finland, 1997.
- [12] R. Thomä, D. Hampicke, A. Richter, G. Sommerkorn, A. Schneider, U. Trautwein, and W. Wirnitzer, "Identification of time-variant directional radio channels," *IEEE Trans. Instrumentation and Measurement*, vol. 49, pp. 357-364, 2000.

- [13] E. Zollinger, J. Pamp, and J. Kunisch, "Measuring Mobile Radio Channels", XXVIth General Assembly of the International Union of Radio Science, Session F1: Mobile Terrestrial and Satellite Propagation Modeling, Aug. 13-21, 1999, University of Toronto, Toronto, Canada.
- [14] B.H. Fleury, D. Dahlhaus, R. Heddergott, and M. Tschudin, "Wideband angle of arrival estimation using the SAGE algorithm," in Proc. IEEE Fourth Int. Symp. spread Spectrum techniques and Applications (ISSSTA'96), Mainz, Germany, pp. 79-85, Sept. 1996.
- [15] B.H. Fleury, "First- and second-order characterization of direction-dispersion and space selectivity in the radio channel," *IEEE Trans. Inform. Theory*, vol. IT-46, no. 6, pp. 2027-2044, Sept. 2000.
- [16] "PropSoundTM, Multi-Dimensional Radio Channel Sounder", product flyer, Elektrobit AG, Switzerland, Oct. 2001.
- [17] B.H. Fleury, P. Jourdan, and A. Stucki, "High-resolution channel parameter estimation for MIMO applications using the SAGE algorithm," 2000 International Zurich Seminar on Broadband Communications (IZS2000), Feb. 15-17 2002, ETH Zurich, Switzerland.
- [18] Bernhard H. Fleury, Martin Tschudin, Ralf Heddergott, Dirk Dahlhaus, and Klaus Ingeman Pedersen, "Channel Parameter Estimation in Mobile Radio Environment Using the SAGE Algorithm," *IEEE Journal on Selected Areas in Communications*, vol. 17, no. 3, pp. 434-450, March 1999.